

Technical Data	C1-140	C1-140B	C1-200	C1-200B
Maximum hose size				
2 wire	1½	1½	2"	2"
4 spiral	1¼	1¼	2"	1¼
Crimping range Ø (mm)	4...61	4...61	4...87	4...87
Die type	140	140	200	200
Max. Opening (mm)	25	25	33	33
Master die D/L (mm)	84/80	84/80	99/80	99/80
Motor (kW)	3	1.5	4	1.5
Standard voltages (V)	380VAC	12VDC	380VAC	12VDC
Crimping force (kN)	1400	1300	1900	1700
Maximum crimping force tonnage	140	130	190	170
Theoretical number of crimpings/hour	600	150	600	120
Overall dimensions				
Lenght (mm)	596	571	596	626
Width (mm)	475	533	543	543
Height (mm)	591	387	591	421
Weight without oil (kg)	135	85	190	115

Standard table of crimping die sets		
Code	Diameter (mm)	L (mm)
140-10	10.0-12.0	55
140-12	12.0-14.0	55
140-14	14.0-16.0	55
140-16	16.0-19.0	55
140-19	19.0-23.0	55
140-23	23.0-27.0	55
140-27	27.0-31.0	70
140-31	31.0-36.0	70
140-36	36.0-41.0	75
140-41	41.0-47.0	75
140-47	47.0-54.0	85
140-54	54.0-61.0	85
200-10	10.0-12.0	55
200-12	12.0-14.0	55
200-14	14.0-16.0	55
200-16	16.0-19.0	55
200-19	19.0-22.0	55
200-22	22.0-26.0	70
200-26	26.0-30.0	70
200-30	30.0-34.0	70
200-34	34.0-39.0	75
200-39	39.0-45.0	75
200-45	45.0-51.0	90
200-51	51.0-57.0	90
200-57	57.0-63.0	100
200-63	63.0-69.0	110
200-69	69.0-74.0	110
200-74	74.0-78.0	110
200-78	78.0-87.0	110



36 Harpur Avenue
P.O. Box 1941
Benoni 1500
South-Africa

